



## Worksheet 4 Thinking logically

### Task 1

1. Use the trace table below to help you answer (a), (b) and (c) below.  
What would be the values of integer variables x, y and z after execution of these statements if the initial values of x and y are:

- (a) 2 and 7  
(b) -4 and -4  
(c) 27 and 3

```

z = x
IF x = y THEN
    x = x * x
    y = (x + y) / 2
ELSE
    IF x < y THEN
        y = y * y
        z = y - x
    ELSE
        IF x > 0 THEN
            z = x/y
        ENDIF
    ENDIF
    y = 200
ENDIF
OUTPUT x, y, z
    
```

#### Trace

x	y	z

2. Use a trace table to determine the output from the following algorithm.

```

x = 5
k = 10
sum = 45
WHILE sum < 75
    sum = sum + k
    OUTPUT k
    k = k + x
ENDWHILE
OUTPUT sum
    
```

x	k	sum	OUTPUT



3. Study the following algorithm and fill in the trace tables below to discover what it does.

```
y = 2
z = 1
OUTPUT ("Please enter a positive integer: ")
x = USERINPUT
WHILE z <> 0
    z = x mod y
    IF z <> 0 THEN
        y = y + 1
    ENDIF
ENDWHILE
IF x = y
    print (x, " is in category 1")
ELSE
    print (x, " is in category 2")
ENDIF
```

x	y	z

x	y	z

- (i) If the user inputs the integer 25, what is output?
- (ii) If the user enters the integer 7, what is output?
- (iii) What are "category 1" and "category 2"? What is the purpose of the program?
- (iv) Suggest ways in which the program could be made easier to understand.



- (v) This is a “brute force” algorithm. Suggest how the algorithm could be made more efficient.

### Task 2

4. Sean has written a program which contains a complex Boolean expression controlling a while loop.

- (a) Complete the truth table for the Boolean expression:

`while ((a > b) or (b > c)) and ((not (a > b)) and (not (b > c)))`

Let P represent  $a > b$  and Q represent  $b > c$

P	Q	not P	not Q	P or Q	Not P and not Q	(P or Q) and (not P and not Q)
False	False					
False	True					
True	False					
True	True					

- (b) How many times will this loop be performed if  $a = 1$ ,  $b = 2$ ,  $c = 3$ ?

How did you calculate your answer?

5. The programmer decides that the condition is not correct. He tries again.

`while (a > b or b > c) or (not (a > b) and not (b > c))`

Complete the truth table for this loop.

P	Q	not P	not Q	P or Q	Not P and not Q	(P or Q) or (not P and not Q)
False	False					
False	True					
True	False					
True	True					



True	False					
------	-------	--	--	--	--	--

How many times will this loop be performed if  $a = 1$ ,  $b = 2$ ,  $c = 3$ ?

### Task 3

6. An Internet site has the following login procedure. To access their account, a customer has to enter

- a 10-character user ID (3 attempts allowed)
- a 4-digit PIN (1 attempt allowed)
- three random characters from their password (3 attempts allowed)

Once the user enters their user ID, a subroutine is called which looks up their record and reads the stored userID, PIN and password.

If the user fails after 3 attempts to enter an ID which is held in the record, a message is displayed "Incorrect ID - access denied"

Similar messages are displayed if the user fails to enter a correct PIN or password

If all details are correct, access to the account is permitted.

- (a) Draw a hierarchy chart to show the tasks and subtasks involved in the login procedure.

- (b) Write pseudocode for a subroutine to check that the user ID exists on a customer file.

- (c) What are the weaknesses in this login procedure? What improvements would you suggest?



### **Task 4**

7. Look up “Benefits of quad-core processor” in a search engine and list some of the benefits and applications which commonly use parallel processing.